







**2 STARK** - Exceeds SAE 100 R16 - EN 857 2 SC  
Extremely high pressure compact hose.



 HOSE I.D.					 HOSE O.D.	 WORKING PRESSURE	 BURST PRESSURE	 MINIMUM BEND RADIUS	 WEIGHT
Item no.	DN	SIZE	MM	INCH	MM	BAR	BAR	MM	KG/mt
2STK-06-04	06	-4	6,4	1/4"	13,1	450	1800	45	0,30
2STK-10-06	10	-6	9,5	3/8"	16,5	390	1560	70	0,38
2STK-12-08	12	-8	12,7	1/2"	20,1	350	1400	90	0,55
2STK-19-12	19	-12	19,0	3/4"	27,5	280	1120	160	0,80

**Applications:**

Recommended for hydraulic applications where a high pressure and a tighter bend radius is needed.  
Suitable for passage of mineral and vegetables oils, water-based solutions, water air and inert gases.

**Construction:**

**Tube:** Black synthetic rubber resistant to oils.  
**Reinforcement:** Two high tensile steel braids.  
**Cover:** Black synthetic rubber resistant to oils, abrasion and weather condition

**Temperature:**

-40°C to 100°C (125°C discontinuous)  
-40°F to 212°F (257°F discontinuous)

**TAON**

Hydraulik Komponenter

**TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tool.**

**TAON Hydraulic Components ApS • +45 24 48 84 80 • info@taon.dk • www.taon.dk**

**© TAON Hydraulic will always help you find the best solution.**